

# SUS304 (固溶化 PM)

状 態		酸 洗	ピーリング	引き抜き品	ネジ下
鋼 種	熱 処 理				
SUS304	S T		●		

○ 残込みでの切断可 ● 切断可

Φmm	標準 長さ mm	メートルあたり 重量(kg)	仕様	在庫	備考
6					
8					
9					
10					
12					
13					
14					
15					
16		STPM	●		
17					
18					
19		STPM	●		
20		STPM	●		
21					
22		STPM	●		
23					
24		STPM	●		
25		STPM	●		
26					
28		STPM	●		
30		STPM	●		
32		STPM	●		
34		STPM	●		
35					
36		STPM	●		
38		STPM	●		
40		STPM	●		
42		STPM	●		
44		STPM	●		
46		STPM	●		
48		STPM	●		
50		STPM	●		
55		STPM	●		
60		STPM	●		
65		STPM	●		

Φmm	標準 長さ mm	メートルあたり 重量(kg)	仕様	在庫	備考
70			STPM	●	
75			STPM	●	
80			STPM	●	
85			STPM	●	
90			STPM	●	
95			STPM	●	
100			STPM	●	
110			STPM	●	
120			STPM	●	
130			STPM	●	
140			STPM	●	
150			STPM	●	
160			STPM	●	
170			STPM	●	
180			STPM	●	
190			STPM	●	
200			STPM	●	